


## Conduit Bodies with Cover & Gasket Combination (EMT/IMC/RIGID) LL Type



### Features

- Set screw and threaded LL type with cover and gasket
- Suitable for use in concrete
- NPT Tapered hubs
- NEMA FB1 rated for wet locations use with threaded rigid metal conduit only

### Applications

- Provides access to conductors for pulling, splicing and maintenance pulling, splicing and maintenance

### Standard Material


- Copper free aluminum die cast
- Steel screws standard finish
- Powder coat



Catalog Number	Size	Wire Size		Unit Carton	Ship Case	Weight / Case	Dimensions (in)		
		Max. Number	Max. Size				A	B	C
LL-50-CG	½"	2	6AWG	10	100	36	4.296	1.310	2.060
LL-75-CG	¾"	2	6AWG	10	50	23	5.090	1.625	2.330
LL-100-CG	1"	3	6AWG	5	25	18	5.915	1.900	2.650
LL-125-CG	1-¼"	3	2AWG	2	10	14	7.894	2.770	3.385
LL-150-CG	1-½"	3	2AWG	2	10	16	7.894	2.770	3.385
LL-200-CG	2"	3	2/0AWG	1	5	14	10.134	3.335	3.810
LL-250-CG	2-½"	3	4/0AWG	—	1	6	12.500	5.437	4.450
LL-300-CG	3"	3	250MCM	—	1	6	12.500	5.657	4.450
LL-350-CG	3-½"	3	350MCM	—	1	8	15.500	6.922	5.500
LL-400-CG	4"	4	350MCM	—	1	8	15.500	6.922	5.500

\*Malleable Iron Conduit Bodies are available upon request

## Combination (EMT/IMC/RIGID) LR Type



### Features

- Set screw and threaded LR type
- Suitable for use in concrete
- NPT Tapered hubs
- NEMA FB1 rated for wet locations use with threaded rigid metal conduit only

### Applications

- Provides access to conductors for pulling, splicing and maintenance

### Standard Material

- Copper free aluminum die cast
- Steel screws

### Standard Finish

- Powder coat



Catalog Number	Size	Wire Size		Unit Carton	Ship Case	Weight / Case	Dimensions (in)		
		Max. Number	Max. Size				A	B	C
LR-50-CG	½"	2	6AWG	10	100	36	4.295	1.310	2.060
LR-75-CG	¾"	2	6AWG	10	50	28	5.090	1.625	2.330
LR-100-CG	1"	3	6AWG	5	25	17	5.915	1.900	2.650
LR-125-CG	1-¼"	3	2AWG	2	10	15	7.894	2.770	3.385
LR-150-CG	1-½"	3	2AWG	2	10	18	7.894	2.770	3.385
LR-200-CG	2"	3	2/0AWG	1	5	14	10.134	3.335	3.810
LR-250-CG	2-½"	3	4/0AWG	—	1	7	12.500	5.437	4.450
LR-300-CG	3"	3	250MCM	—	1	7	12.500	5.657	4.450
LR-350-CG	3-½"	3	350MCM	—	1	10	15.500	6.922	5.500
LR-400-CG	4"	4	350MCM	—	1	10	15.500	6.922	5.500

\*Malleable Iron Conduit Bodies are available upon request