


Conduit Bodies With Cover and Gasket

Combination (EMT/IMC/RIGID)

LB Type



Features

- Set screw and threaded LB type with cover and gasket
- Suitable for use in concrete
- NPT Tapered hubs
- NEMA FB1 rated for wet locations use with threaded rigid metal conduit only

Applications

- Provides access to conductors for pulling, splicing and maintenance

Standard Material

- Copper free aluminum die cast
- Steel screws standard finish
- Powder coat




Catalog Number	Size	Wire Size		Unit Carton	Ship Case	Weight / Case	Dimensions (in)		
		Max. Number	Max. Size				A	B	C
LB-50-CG	1/2"	2	6AWG	10	100	29	4.560	2.060	1.310
LB-75-CG	3/4"	2	6AWG	10	50	23	5.090	2.430	1.540
LB-100-CG	1"	3	6AWG	5	25	19	5.915	2.765	1.740
LB-125-CG	1-3/8"	3	2AWG	2	10	14	7.894	3.665	2.490
LB-150-CG	1-1/2"	3	2AWG	2	10	15	7.894	3.665	2.490
LB-200-CG	2"	3	2/0AWG	1	5	14	10.134	4.275	3.100
LB-250-CG	2-1/2"	3	2/0AWG	—	1	7	12.500	5.437	4.450
LB-300-CG	3"	3	4/0AWG	—	1	7	12.500	5.657	4.450
LB-350-CG	3-1/2"	3	500MCM	—	1	10	15.500	6.922	5.500
LB-400-CG	4"	3	500MCM	—	1	10	15.500	6.922	5.500

*Malleable Iron Conduit Bodies are available upon request

Combination (EMT/IMC/RIGID)

C Type



Features

- Suitable Set screw and threaded C type with cover and gasket for use in concrete
- NPT Tapered hubs
- NEMA FB1 rated for wet locations use with threaded rigid metal conduit only

Applications

- Provides access to conductors for pulling, splicing and maintenance

Standard Material

- Copper free aluminum die cast
- Steel screws
- Standard Finish
- Powder coat



Catalog Number	Size	Wire Size		Unit Carton	Ship Case	Weight / Case	Dimensions (in)		
		Max. Number	Max. Size				A	B	C
C-50-CG	1/2"	2	6AWG	5	100	30	4.720	1.370	1.330
C-75-CG	3/4"	2	6AWG	5	50	21	5.570	1.625	1.540
C-100-CG	1"	3	6AWG	5	25	25	6.460	1.900	15.500
C-125-CG	1-3/8"	3	2AWG	5	25	15	8.528	2.770	2.490
C-150-CG	1-1/2"	3	2AWG	5	10	17	8.528	2.770	2.490
C-200-CG	2"	3	2/0AWG	1	5	13	10.831	3.335	3.100
C-250-CG	2-1/2"	3	4/0AWG	—	1	6	13.000	4.063	5.709
C-300-CG	3"	3	250MCM	—	1	6	12.500	4.682	5.506
C-350-CG	3-1/2"	3	350MCM	—	1	8	—	5.452	6.171
C-400-CG	4"	4	350MCM	—	1	8	15.500	5.452	6.171

*Malleable Iron Conduit Bodies are available upon request