

Rigid Connectors

Set Screw Type - Steel



Features

- Concrete tight when taped
- Threadless

Applications

- Used to join unthreaded Rigid or IMC conduit to steel outlet box or metal enclosure

Standard Material

- Steel

Standard Finish

- Zinc plated

Catalog Number	Size	Unit Carton	Ship Case	Weight/Case	Dimensions (in)	
					A	B
C-RCN050	½"	20	200	13	1.398	0.886
C-RCN075	¾"	10	100	20	1.496	1.063
C-RCN100	1"	5	50	36	1.720	1.378
C-RCN125	1-¼"	5	50	64	1.890	1.700
C-RCN150	1-½"	—	12	92	2.126	1.992
C-RCN200	2"	—	12	117	2.056	2.429
C-RCN250	2-½"	—	5	14	3.000	3.750
C-RCN300	3"	—	3	13	3.125	4.250
C-RCN350	3-½"	—	2	13	3.187	4.750
C-RCN400	4"	—	2	13	3.437	5.312

Rigid Couplings

Set Screw Type - Steel



Features

- Compression type
- Concrete tight
- Threadless

Applications

- Used to join two lengths unthreaded Rigid or IMC conduit to steel outlet box or metal enclosure

Standard Material

- Steel

Standard Finish

- Zinc plated

Catalog Number	Size	Unit Carton	Ship Case	Weight/Case	Dimensions (in)	
					A	B
C-RCP050	½"	10	100	16	1.799	0.875
C-RCP075	¾"	10	100	24	2.055	1.086
C-RCP100	1"	5	50	48	2.087	1.338
C-RCP125	1-¼"	5	50	86	2.512	1.732
C-RCP150	1-½"	—	12	125	2.563	1.990
C-RCP200	2"	—	5	160	2.350	2.422
C-RCP250	2-½"	—	5	260	5.750	3.930
C-RCP300	3"	—	3	300	5.720	4.660
C-RCP350	3-½"	—	2	350	6.000	5.200
C-RCP400	4"	—	2	400	6.810	5.750

*Malleable iron materials are also available. Please add "M" to the Part Number while ordering "R-CCN075M, R-CCP075M, etc..."