


Flex Couplings

Screw In Type



Features

- Screw in coupling

Applications

- Indoor use only
- Use to join two pieces of flexible metallic conduit


Standard Material

- Zinc die cast

Catalog Number	Conduit Size	Unit Carton	Ship Case	Weight/Case	Dimensions (in)		
					A	B	C
CPFF050	½"	50	500	30	1.80	0.92	1.062
CPFF075	¾"	25	250	23	2.09	1.12	1.372
CPFF100	1"	25	250	38	2.41	1.37	1.687
CPFF125	1-¼"	10	100	25	2.74	1.81	2.125
CPFF150	1-½"	10	40	16	3.05	2.12	2.375
CPFF200	2"	10	40	24	3.27	2.67	2.937

Combination Couplings

Set Screw Type - EMT to Flex



Features

- Set screw type
- EMT to flex combination coupling
- UL listed

Applications

- Indoor use only
- Use to join EMT conduit to flexible metal conduit

Standard Material

- Zinc die cast

Catalog Number	Size	Unit Carton	Ship Case	Weight/Case	Dimensions (in)		
					A Min.	A Max.	B
CPEF050S	½" - ½"	25	250	25	0.75	0.95	1.65
CPEF075S	¾" - ¾"	—	100	15	0.75	1.20	1.93
CPEF100S	1" - 1"	—	50	13	1.14	1.61	2.12