


Rigid Connectors

Compression Type - Steel



Features

- Concrete tight when taped
- Threadless

Applications

- Used to join unthreaded Rigid or IMC conduit to steel outlet box or metal enclosure

Standard Material

- Steel


Standard Finish

- Zinc plated

Catalog Number	Size	Unit Carton	Ship Case	Weight/Case	Dimensions (in)	
					A	B
R-CCN050	½"	20	200	13	1.398	0.886
R-CCN075	¾"	10	100	20	1.496	1.063
R-CCN100	1"	5	50	36	1.720	1.378
R-CCN125	1-¼"	5	50	64	1.890	1.700
R-CCN150	1-½"	—	12	92	2.126	1.992
R-CCN200	2"	—	12	117	2.056	2.429
R-CCN250	2-½"	—	5	14	3.000	3.750
R-CCN300	3"	—	3	13	3.125	4.250
R-CCN350	3-½"	—	2	13	3.187	4.750
R-CCN400	4"	—	2	13	3.437	5.312

Rigid Couplings

Compression Type - Steel



Features

- Compression type
- Concrete tight
- Threadless

Applications

- Used to join two lengths unthreaded Rigid or IMC conduit to steel outlet box or metal enclosure

Standard Material

- Steel

Standard Finish

- Zinc plated

Catalog Number	Size	Unit Carton	Ship Case	Weight/Case	Dimensions (in)	
					A	B
R-CCP050	½"	10	100	16	1.799	0.875
R-CCP075	¾"	10	100	24	2.055	1.086
R-CCP100	1"	5	50	48	2.087	1.338
R-CCP125	1-¼"	5	50	86	2.512	1.732
R-CCP150	1-½"	—	12	125	2.563	1.990
R-CCP200	2"	—	5	160	2.350	2.422
R-CCP250	2-½"	—	5	260	5.750	3.930
R-CCP300	3"	—	3	300	5.720	4.660
R-CCP350	3-½"	—	2	350	6.000	5.200
R-CCP400	4"	—	2	400	6.810	5.750

*Malleable iron materials are also available. Please add "M" to the Part Number while ordering "R-CCN075M, R-CCP075M, etc..."