


Combination Couplings

Screw In Type - EMT Compression to Flex - Zinc Die Cast



Features

- Screw in to compression type
- Combination coupling used to join flexible metal conduit to EMT

Applications


- Indoor use only
- Use to join EMT conduit to flexible metallic conduit
- Suitable for: 1/2" steel, steel reduced wall, and aluminum flexible metal conduit to EMT, 3/4"-1" flexible metal conduit to EMT

Standard Material

- Zinc die cast

Catalog Number	Size	Unit Carton	Ship Case	Weight/Case	Dimensions (in)		
					A	B	C
CPEF050	1/2" - 1/2"	50	500	40	1.660	1.000	0.723
CPEF075	3/4" - 3/4"	25	250	28	1.680	1.180	0.931
CPEF100	1" - 1"	25	250	58	1.895	1.625	1.070

Compression Type EMT to Rigid - Steel



Features

- Internally threaded for Rigid/IMC conduit
- Compression type EMT
- Raintight

Applications

- Indoor use only
- Use to join Rigid/IMC conduit to EMT between 2 different raceways
- Coupling internally threaded for Rigid/IMC
- Compression type for EMT, concrete tight

Standard Material

- Steel

Standard Material

- Zinc plated

Catalog Number	Size	Unit Carton	Ship Case	Weight/Case	Dimensions (in)	
					A	B
CPER050	1/2"	20	200	31	1.100	1.570
CPER075	3/4"	10	100	21	1.330	1.620
CPER100	1"	10	100	30	1.630	1.820