


Combination Couplings

Liquidtight to Rigid - Steel / Zinc Die Cast



Features

- Raintight
- Liquidtight
- NPSM thread
- Labor saving

Applications


- Use to join liquidtight metal conduit (LFMC) to Rigid/IMC conduit between 2 different raceways
- Suitable for use in wet locations
- Raintight, concrete tight

Standard Material

- Steel / Die Cast Zinc Standard Finish
- Zinc plated

Catalog Number	Size	Unit Carton	Ship Case	Weight/Case	Dimensions (in)	
					A	B
E-LFC 50	½"	20	200	29	1.17"	1.78"
E-LFC 75	¾"	10	100	23	1.43"	1.94"
E-LFC 100	1"	5	50	18	1.76"	2.19"
E-LFC 125	1-¼"	5	50	30	2.16"	2.23"
E-LFC 150	1-½"	-	12	8	2.38"	2.62"
E-LFC 200	2"	-	5	5	2.87"	2.67"

Liquidtight to EMT - Steel / Zinc Die Cast



Features

- EMT to liquidtight
- Set screw type
- Reusable ferrule

Applications

- Use to connect LT conduit to EMT ½" thru 1", ideal for rooftop HVAC air conditioners and motor hook-ups
- Can be used with EMT indoors only

Standard Material

- Steel / Die Cast Zinc Standard Finish
- Zinc plated

Catalog Number	Size	Unit Carton	Ship Case	Weight/Case	Dimensions (in)		
					A	B	C
E-LSC 50	½" - ½"	25	250	20	1.64	1.39	1.09
E-LSC 75	¾" - ¾"	20	200	14	1.75	1.72	1.30
E-LSC 100	1" - 1"	10	100	16	2.00	1.75	1.50