


## Pull Elbows with Gasket

Rigid to Rigid



### Features

- Low conductivity, high corrosion resistance
- Smooth defect free interior and exterior

### Applications

- For a secure connection to EMT conduit; bend enables directional changes in conduit


### Standard Material

- Galvanized steel

Catalog Number	Size	Unit Carton	Ship Case	Weight/Case	Dimensions (in)			
					A	B	C	D
PE-RR050	½"	10	100	28	1.310	1.090	2.500	1.780
PE-RR075	¾"	5	50	17	1.430	1.290	2.760	2.130
PE-RR100	1"	—	25	16	1.950	1.590	3.860	3.170
PE-RR125	1-¼"	—	20	18	2.260	1.970	4.560	3.250

## Pull Elbows with Gasket

Rigid to Box



### Features

- Rigid to Rigid
- Removable cover facilitates wire pulling
- Neoprene gasket

### Applications

- Indoor or outdoor use (Rigid only)
- Use as a wire pulling elbow to facilitate wire pulling through a sharp bend in a run of threaded Rigid or IMC conduit
- Can be used with EMT indoors only

### Standard Material

- Zinc die cast
- Neoprene gasket

Catalog Number	Size	Unit Carton	Ship Case	Weight/Case	Dimensions (in)			
					A	B	C	D
PE-RB050	½"	10	100	31	1.310	1.090	2.400	1.800
PE-RB075	¾"	5	50	18	1.470	1.290	2.660	2.140
PE-RB100	1"	—	25	21	2.800	1.600	3.660	3.160
PE-RB125	1-¼"	—	20	25	3.130	1.960	5.160	3.240