

## Rigid Bushings

Insulated - 105°C Thermoplastic Liner - Zinc Die Cast



### Features

- Liner is rated flame retardant to 105°C

### Applications


- Indoor or outdoor use
- Use with locknut to terminate Rigid or IMC conduit to an outlet box
- Plastic liner prevents damage to wire insulation

### Standard Material

- Zinc die cast
- Plastic insulator

Catalog Number	Size	Unit Carton	Ship Case	Weight/Case	Dimensions (in)	
					A	B
C-RBI050	3/8"	130	1000	30	0.950	0.350
C-RBI075	3/4"	50	500	20	1.100	0.390
C-RBI100	1"	50	500	40	1.460	0.430
C-RBI125	1-3/8"	25	250	25	1.840	0.470
C-RBI150	1-3/4"	25	250	30	2.000	0.510
C-RBI200	2"	—	100	14	2.570	0.550
C-RBI250	2-3/4"	—	50	20	3.130	0.630
C-RBI300	3"	—	25	12	3.770	0.790
C-RBI350	3-3/4"	—	25	14	4.350	0.860
C-RBI400	4"	—	10	6	4.800	0.810
C-RBI500	5"	—	5	10	6.150	1.300
C-RBI600	6"	—	5	12	7.250	1.125

## Insulated Grounding Bushing with Aluminium Lay-In Lug



### Features & Applications:

- Use to provide a means of grounding Rigid or IMC Conduit
- Use with locknut to terminate service conduit to a cabinet
- Lug provided for bonding jumper to a neutral bus bar
- Round surface of bushing prevents damage to wire insulation
- Plastic liner prevents damage to wire insulation

### Standard Material:

- Rigid Malleable Iron
- Plastic Insulator
- Lug-Aluminum
- Clamping screw-Steel
- Set screw Steel

Catalog Number	Size	Grounding Lug Wire Size		Unit Carton	Ship Case	Weight/Case	Dimensions (in)	
		Min.	Max.				A	B
RBIG050	3/8"	14	4	50	500	30	0.830	0.550
RBIG075	3/4"	14	4	50	500	35	1.260	0.710
RBIG100	1"	14	4	25	250	23	1.580	0.980
RBIG125	1-3/8"	14	4	20	200	26	1.980	1.290
RBIG150	1-3/4"	14	4	10	100	16	2.150	1.480
RBIG200	2"	14	4	10	100	21	2.650	1.810
RBIG250	2-3/4"	14	1/0	—	50	20	3.190	2.240
RBIG300	3"	14	1/0	—	50	29	3.820	2.840
RBIG400	4"	14	1/0	—	10	15	4.800	3.820