


Watertight Conduit Hubs

Insulated Throat - Zinc Die Cast



Features

- Flame-retardant insulated throat
- Rain, oil, and dust tight
- Oversized locknut prevents damage from vibrations and promotes positive grounding

Applications


- Indoor or outdoor use
- Use to connect Rigid or IMC conduit to a load center or other metal enclosure where a watertight joint is required at knockouts or slip-fit holes

Standard Material

- Zinc die cast

| Catalog Number | Size | Unit Carton | Ship Case | Weight/Case | Dimensions (in) | |
|----------------|------|-------------|-----------|-------------|-----------------|-------|
| | | | | | A | B |
| R-WH050 | ½" | 25 | 250 | 49 | 1.299 | 1.339 |
| R-WH075 | ¾" | 10 | 100 | 29 | 1.496 | 1.634 |
| R-WH100 | 1" | 10 | 100 | 42 | 1.654 | 1.890 |
| R-WH125 | 1-¼" | 2 | 20 | 12 | 1.811 | 2.303 |
| R-WH150 | 1-½" | 2 | 20 | 15 | 1.772 | 2.559 |
| R-WH200 | 2" | 2 | 10 | 9 | 1.909 | 3.150 |
| R-WH250 | 2-½" | — | 5 | 8 | 2.126 | 3.858 |
| R-WH300 | 3" | — | 5 | 9 | 2.579 | 4.291 |
| R-WH350 | 3-½" | — | 5 | 11 | 2.440 | 4.880 |
| R-WH400 | 4" | --- | 1 | 3 | 2.677 | 5.394 |

With Bonding Screw - Zinc Die Cast



Features

- Flame-retardant insulated throat
- Rain, oil, and dust tight
- Oversized locknut prevents damage from vibrations and promotes positive grounding

Applications

- Indoor or outdoor use
- Use to connect Rigid or IMC conduit to a load center or other metal enclosure where a watertight joint is required at knockouts or slip-fit holes

Standard Material

- Zinc die cast

| Catalog Number | Size | Unit Carton | Ship Case | Weight/Case | Dimensions (in) | |
|----------------|------|-------------|-----------|-------------|-----------------|-------|
| | | | | | A | B |
| R-WH050B | ½" | 25 | 250 | 53 | 1.299 | 1.339 |
| R-WH075B | ¾" | 10 | 100 | 30 | 1.496 | 1.634 |
| R-WH100B | 1" | 10 | 100 | 43 | 1.654 | 1.890 |
| R-WH125B | 1-¼" | 2 | 20 | 12 | 1.811 | 2.303 |
| R-WH150B | 1-½" | 2 | 20 | 15 | 1.772 | 2.559 |
| R-WH200B | 2" | 2 | 20 | 10 | 1.909 | 3.150 |
| R-WH250B | 2-½" | — | 2 | 8 | 2.126 | 3.858 |
| R-WH300B | 3" | — | 2 | 10 | 2.579 | 4.291 |
| R-WH350B | 3-½" | — | 1 | 13 | 2.440 | 4.880 |
| R-WH400B | 4" | — | 1 | 15 | 2.677 | 5.394 |

*Malleable iron materials are also available. Please add "M" to the Part Number while ordering "R-WH075M, R-WH075BM, etc..."