

Flexible Squeeze Connectors

Straight - Squeeze Type - Zinc Die Cast



Features


- Squeeze type straight
- Available with insulated throat

Applications

- Indoor use only
- In a dry location, use to connect flexible metallic conduit to a steel outlet box, load center or other metal enclosure

Standard Material

- Zinc die cast



Catalog Number	Size	Unit Carton	Ship Case	Weight/Case	Dimensions (in)			Screws
					A	B	C	
CFSC050	½"	25	250	25	1.378	0.563	0.394	1
CFSC075	¾"	25	250	32	1.496	1.114	0.433	1
CFSC100	1"	10	100	20	1.673	1.389	0.492	1
CFSC125	1-¼"	10	100	29	1.862	1.642	0.563	1
CFSC150	1-½"	5	50	20	1.957	1.961	0.691	1
CFSC200	2"	10	40	21	2.134	2.461	0.669	1
CFSC250	2-½"	—	10	9	2.815	2.362	0.847	2
CFSC300	3"	—	10	17	3.209	2.953	0.847	2
CFSC350	3-½"	—	1	3	4.190	3.750-4.100	1.030	2
CFSC400	4"	—	1	3	3.957	3.819	0.886	2

* Insulated models are also available. Please add "-I" to the part number while ordering (CFSC050I)

90° - Squeeze Type - Zinc

Features


- Squeeze type

Applications

- Indoor use only
- In a dry location, use to connect flexible metal conduit to a steel outlet box or other metal enclosure

Standard Material

- Zinc die cast
- Zinc plated steel strap



Catalog Number	Size	Unit Carton	Ship Case	Weight/Case	Dimensions (in)			Screws
					A	B (Min.-Max.)	C	
CFSC9050	½"	25	250	35	2.110	0.640-1.030	0.400	2
CFSC9075	¾"	10	100	20	2.400	0.760-1.150	0.400	2
CFSC9100	1"	5	50	19	2.870	1.090-1.730	0.540	2
CFSC9125	1-¼"	10	40	20	4.000	1.340-1.970	0.640	2
CFSC9150	1-½"	---	5	5	6.000	1.650-2.610	0.750	2
CFSC9200	2"	---	5	6	6.000	1.540-2.540	0.740	2
CFSC9250	2-½"	---	5	18	7.187	2.450-2.980	0.875	4
CFSC9300	3"	---	2	9	7.875	2.930-3.450	1.031	4
CFSC9350	3-½"	---	1	9	9.400	3.280-3.950	1.031	4
CFSC9400	4"	---	1	10	10.200	3.680-4.430	1.031	4

* Insulated models are also available. Please add "-I" to the part number while ordering (CFSC9050I)