


Straight Liquidtight Connectors

Zinc



Features

- Straight component type connectors
- Assembled with a die cast locknut

Applications

- To secure, ground and seal liquidtight conduit to a box or enclosure

Standard Material


- Zinc die cast



Catalog Number	Size	Unit Carton	Ship Case	Weight/Case	Dimensions (in)		
					A	B	C
CFLT050	½"	20	200	40	1.283	1.209	0.484
CFLT075	¾"	10	100	23	1.527	1.244	0.488
CFLT100	1"	5	50	20	1.772	1.457	0.591
CFLT125	1-¼"	5	50	30	2.213	1.725	0.669
CFLT150	1-½"	2	20	15	2.480	1.756	0.669
CFLT200	2"	2	20	24	2.953	1.732	0.630
CFLT250	2-½"	---	1	1	3.543	2.559	0.945
CFLT300	3"	---	1	2	4.252	2.795	0.984
CFLT350	3-½"	---	1	3	3.660	5.470	0.920
CFLT400	4"	---	1	4	5.236	2.992	1.102

90° Liquidtight Connectors

Zinc



Features

- 90° component type connectors
- Assembled with a die cast locknut

Applications

- To secure, ground and seal liquidtight conduit to a box or enclosure

Standard Material

- Zinc die cast



Catalog Number	Size	Dimensions (in)				TPI (N1)	TPI (N2)	No of Lock nuts used
		A	B	C	D			
CFLT9050	½"	1.490	1.409	1.283	0.565	18	14	1
CFLT9075	¾"	1.606	1.606	1.527	0.747	18	14	1
CFLT9100	1"	1.976	1.976	1.772	0.949	18	11.5	1
CFLT9125	1-¼"	2.256	2.256	2.212	1.248	16	11.5	1
CFLT9150	1-½"	2.492	2.492	2.480	1.516	16	11.5	1
CFLT9200	2"	2.811	2.811	2.953	1.909	16	11.5	1
CFLT9250	2-½"	4.259	4.259	3.543	2.402	14	8	1
CFLT9300	3"	3.961	3.961	4.252	2.961	14	8	1
CFLT9400	4"	4.134	4.134	5.236	3.799	14	8	1