


## Straight Liquidtight Connectors

With Grounding Lug - Zinc / Malleable Iron



### Features

- Liquidtight
- Lay-in grounding lug
- Insulated throat protects conductors from abrasion damage
- Zinc electro plated for excellent durability

### Applications

- Use to connect liquidtight conduit and terminate an external bonding conductor that runs parallel to the conduit

### Standard Material

- Zinc / Malleable iron
- Steel locknut
- Aluminum lug


### Standard Finish

- Zinc plated

Catalog Number	Size	Lug Size	Ship Case	Weight/Case	Dimensions (in)	
					A	B
E-LTC 50-GR	½"	14-4	10	100	1.360	1.730
E-LTC 75-GR	¾"	14-4	5	50	1.610	1.810
E-LTC 100-GR	1"	14-4	5	50	1.890	1.850
E-LTC 125-GR	1-¼"	14-4	2	20	2.390	2.050
E-LTC 150-GR	1-½"	14-4	2	20	2.620	2.380
E-LTC 200-GR	2"	14-4	2	20	3.240	2.490
E-LTC 250-GR	2-½"	1/0-14	---	1	3.890	3.210
E-LTC 300-GR	3"	1/0-14	---	1	4.740	3.370
E-LTC 350-GR	3-½"	6/250	---	1	5.310	3.400
E-LTC 400-GR	4"	6/250	---	1	5.820	3.660

## 90° Liquidtight Connectors

With Grounding Lug - Zinc / Malleable Iron



### Features

- Liquidtight
- Lay-in grounding lug
- Insulated throat protects conductors from abrasion damage
- Zinc electro plated for excellent durability

### Applications

- Use to connect liquidtight conduit and terminate an external bonding conductor that runs parallel to the conduit

### Standard Material

- Zinc / Malleable iron
- Steel locknut
- Aluminum lug

### Standard Finish

- Zinc plated

Catalog Number	Size	Lug Size	Unit Carton	Ship Case	Weight/Case	Dimensions (in)		
						A	B	C
E-LTC 50-90-GR	½"	14-4	5	50	24	1.360	2.100	2.540
E-LTC 75-90-GR	¾"	14-4	2	20	16	1.610	2.450	2.820
E-LTC 100-90-GR	1"	14-4	2	20	17	1.890	2.830	3.080
E-LTC 125-90-GR	1-¼"	14-4	2	20	25	2.390	3.150	3.530
E-LTC 150-90-GR	1-½"	14-4	2	20	29	2.620	3.500	4.170
E-LTC 200-90-GR	2"	14-4	2	20	42	3.240	4.020	4.690
E-LTC 250-90-GR	2-½"	1/0-14	---	1	9	3.890	6.230	6.740
E-LTC 300-90-GR	3"	1/0-14	---	1	11	4.740	6.910	7.520
E-LTC 350-90-GR	3-½"	6/250	---	1	13	5.310	7.570	7.930
E-LTC 400-90-GR	4"	6/250	---	1	15	5.820	8.070	8.720