


EMT Elbows

90° - Galvanized Steel



Catalog Number	Size	Ship Case	Weight/Case	(A) Min. UL Radius	(B) Straight Leg Each End	(C) Offset
EL-9050	½"	50	12	4.000	2.875	6.343
EL-9075	¾"	50	22	4.500	2.875	6.781
EL-9100	1"	20	16	5.750	3.000	8.901
EL-9125	1-¼"	20	29	7.250	3.250	10.250
EL-9150	1-½"	10	20	8.250	3.625	11.937
EL-9200	2"	10	27	9.500	4.187	14.031
EL-9250	2-½"	50	6	10.500	5.250	16.000
EL-9300	3"	35	9	13.000	5.812	18.947
EL-9350	3-½"	35	11	15.000	6.750	22.218
EL-9400	4"	25	15	16.000	6.937	23.437

Features

- Low conductivity, high corrosion resistance
- Smooth defect free interior and exterior

Applications

- For a secure connection to EMT conduit; bend enables directional changes in conduit


Standard Material

- Galvanized steel



EMT Elbows

45° - Galvanized Steel



Catalog Number	Size	Ship Case	Weight/Case	(A) Min. UL Radius	(B) Straight Leg Each End
EL-4050	½"	50	11	4.000	2.875
EL-4075	¾"	50	19	4.500	2.875
EL-4100	1"	35	25	5.750	3.000
EL-4125	1-¼"	30	30	7.250	3.250
EL-4150	1-½"	15	44	8.250	3.625
EL-4200	2"	15	31	9.500	4.187
EL-4250	2-½"	1	5	10.500	5.250
EL-4300	3"	1	7	13.000	5.812
EL-4350	3-½"	1	9	15.000	6.750
EL-4400	4"	1	12	16.000	6.937

Features

- Low conductivity, high corrosion resistance
- Smooth defect free interior and exterior

Applications

- For a secure connection to EMT conduit; bend enables directional changes in conduit

Standard Material

- Galvanized steel

