


Rigid Elbows

90° - Galvanized Steel



Features

- Low conductivity, high corrosion resistance
- Smooth defect free interior and exterior

Applications

- For a secure connection to Rigid conduit; bend enables directional changes in conduit

Standard Material


- Galvanized steel

Catalog Number	Size	Ship Case	Weight/Case	(A) Min. UL Radius	(B) Straight Leg Each End	(C) Offset
RL9050	½"	50	40	4.00	2.875	6.343
RL9075	¾"	50	54	4.50	2.875	6.781
RL9100	1"	20	40	5.750	3.000	8.901
RL9125	1-¼"	20	60	7.250	3.250	10.250
RL9150	1-½"	10	42	8.250	3.625	11.937
RL9200	2"	10	68	9.50	4.187	14.031
RL9250	2-½"	1	13	10.50	5.250	16.000
RL9300	3"	1	18	13.00	5.812	18.947
RL9350	3-½"	1	26	15.00	6.750	22.218
RL9400	4"	1	33	16.00	6.937	23.437
RL9500	5"	1	45	24.00	11.120	36.156
RL9600	6"	1	48	30.00	12.437	41.460



Rigid Elbows

45° - Galvanized Steel



Features

- Low conductivity, high corrosion resistance
- Smooth defect free interior and exterior

Applications

- For a secure connection to Rigid conduit; bend enables directional changes in conduit

Standard Material

- Galvanized steel

Catalog Number	Size	Ship Case	Weight/Case	(A) Min. UL Radius	(B) Straight Leg Each End
RL4050	½"	50	26	4.000	2.875
RL4075	¾"	50	38	4.500	2.875
RL4100	1"	35	45	5.750	3.000
RL4125	1-¼"	30	60	7.250	3.250
RL4150	1-½"	15	45	8.250	3.625
RL4200	2"	15	68	9.500	4.187
RL4250	2-½"	1	8	10.500	5.250
RL4300	3"	1	13	13.000	5.812
RL4350	3-½"	1	16	15.000	6.750
RL4400	4"	1	22	16.000	6.937
RL4500	5"	1	45	24.000	8.125
RL4600	6"	1	71	30.000	13.250

